416 Rec'd PCT/PTO 2 4 FEB 2000

FORM 1	PTO-139	0 (Modified) U.S. DEPARTMENT	T OF COMMERCE PATENT AND TRADEMARK OFFICE	ATTORNEY'S DOCKET NUMBER			
(REV 10	0-95)	RANSMITTAL LETTER	1041				
	11	-					
		DESIGNATED/ELECT	U.S. APPLICATION NO. (IF KNOWN, SEE 37 CFR				
		CONCERNING A FILIN	09/486307				
INTE		IONAL APPLICATION NO.	INTERNATIONAL FILING DATE	PRIORITY DATE CLAIMED			
TOTAL I		PCT/DE 98/01914	JULY 9, 1998	AUGUST 29, 1997			
		NVENTION IC MACHINE IN PARTIC	CULAR A THREE-PHASE GENËRAT	OR			
	CIN	ie machine, in i antic	OLAKA IIII III III GENERATI				
A DDI	IC ANY	Γ(S) FOR DO/EO/US					
		REUZER					
Appli	icant l	nerewith submits to the United St	ates Designated/Elected Office (DO/EO/US) tl	he following items and other information:			
1.	×		items concerning a filing under 35 U.S.C. 371				
2.			QUENT submission of items concerning a filir				
3.			-				
3. This is an express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).							
4.	\boxtimes	A proper Demand for Internation	onal Preliminary Examination was made by the	e 19th month from the earliest claimed priority date.			
5.	\boxtimes	A copy of the International App	olication as filed (35 U.S.C. 371 (c) (2))				
1		a. is transmitted herewith (required only if not transmitted by the International Bureau).					
į		b. 🛭 has been transmitted b	by the International Bureau.				
	c. is not required, as the application was filed in the United States Receiving Office (RO/US).						
6.	☑ A translation of the International Application into English (35 U.S.C. 371(c)(2)).						
7.		A copy of the International Sea	copy of the International Search Report (PCT/ISA/210).				
8.		Amendments to the claims of the	ne International Application under PCT Article	e 19 (35 U.S.C. 371 (c)(3))			
		a. are transmitted herewi	are transmitted herewith (required only if not transmitted by the International Bureau).				
		b. \square have been transmitted by the International Bureau.					
b. ⋈ has been transmitted by the International Bureau. c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/ 6. ⋈ A translation of the International Application into English (35 U.S.C. 371(c)(2)). 7. ☐ A copy of the International Search Report (PCT/ISA/210). 8. ☐ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371 a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau). b. ☐ have been transmitted by the International Bureau. c. ☐ have not been made; however, the time limit for making such amendments has NOT expenditure.				lments has NOT expired.			
		d. \square have not been made and will not be made.					
9.		A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).					
10.	X	An oath or declaration of the inventor(s) (35 U.S.C. 371 (c)(4)).					
11.		A copy of the International Preliminary Examination Report (PCT/IPEA/409).					
11.		A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371 (c)(5)).					
1	tems 1	13 to 18 below concern docume	nt(s) or information included:				
13.	× ×						
14.	×	An Information Disclosure Statement under 37 CFR 1.97 and 1.98. An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.					
15.	X	A FIRST preliminary amendment.					
1	A SECOND or SUBSEQUENT preliminary amendment.						
16.		A SECOND of SUBSEQUENT preliminary amendment. A substitute specification.					
17.		A change of power of attorney and/or address letter.					
18.	X	Certificate of Mailing by Express Mail					
19.		Other items or information:					
			FK 0662	011029111			
		EK 069304032US					
	7						
Ì							

514 Rec'd PCT/PTO 2 4 FEB 2000

U.S. APPLICATION	NO. (IF KNOWN SEE 37 CEP INTERNATIONAL APPLICATION NO. PCT/DE 98/01914				ATTORNEY'S DOCKET NUMBER 1041		
20. The fo	llowing fees are submitted:.	•			CA	LCULATIONS	PTO USE ONLY
	AL FEE (37 CFR 1.492 (a) (1) -						
_	ort has been prepared by the EPO			930.00			
	al preliminary examination fee pai	-		0.00			:
☐ No internati but internati	ional preliminary examination fee ional search fee paid to USPTO (3	paid to USPTO (37 CFR 1.7 CFR 1.445(a)(2))		790.00			
Neither inte internationa	Neither international preliminary examination fee (37 CFR 1.482) nor international search fee (37 CFR 1.445(a)(2) paid to USPTO						
Internationaland all clair	al preliminary examination fee pains satisfied provisions of PCT Art	d to USPTO (37 CFR 1.482 icle 33(2)-(4)		\$98.00			
	ENTER APPROPRI	ATE BASIC FEE A	MOUN	T =		\$970.00	
Surcharge of \$130. months from the ea	00 for furnishing the oath or declar rliest claimed priority date (37 C	ration later than FR 1.492 (e)).	3 20	□ 30		\$0.00	
CLAIMS	NUMBER FILED	NUMBER EXTRA	F	RATE			
Total claims	6 - 20 =	0	x	\$18.00		\$0.00	
Independent claims	1 - 3=	0	x	\$78.00	_	\$0.00	
Multiple Depender	nt Claims (check if applicable).				ļ	\$0.00	
		ABOVE CALCUL			ļ	\$970.00	
must also be filed	or filing by small entity, if applica (Note 37 CFR 1.9, 1.27, 1.28) (ch	ble. Verified Small Entity eck if applicable).	Statement			\$0.00	
Processing fee of \$		St	UBTOT.	AL =		\$970.00	
Processing fee of \$ months from the ea	130.00 for furnishing the English rliest claimed priority date (37 C	translation later than FR 1.492 (f)).	20	□ 30 +		\$0.00	
		TOTAL NATION	NAL FE	E =	1	\$970.00	
Fee for recording the accompanied by an	he enclosed assignment (37 CFR 1 appropriate cover sheet (37 CFR	1.21(h)). The assignment m 3.28, 3.31) (check if appli	ust be cable).	×		\$40.00	
	TOTAL FEES ENCLOSED =				1	\$1,010.00	
						ount to be: refunded	\$
							\$
A check in the amount of \$1,010.00 to cover the above fees is enclosed. Please charge my Deposit Account No. in the amount of to cover the above fees.							
A duplicate copy of this sheet is enclosed. The Commissioner is hereby authorized to charge any fees which may be required, or credit any overpayment to Deposit Account No. 19-4675 A duplicate copy of this sheet is enclosed. NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR 1.137(a) or (b)) must be filed and granted to restore the application to pending status.							
SEND ALL CORRESPONDENCE TO:							
STRIKER STRIKER & STENBY							
103 EAST NECK ROAD HUNTINGTON, NEW YORK 11743 SIGNATIVE MICHAEL J. STRIKER							
1					J. S1.	RIKER	
Į.			NAI				
			272				
			REC	GISTRAT	ON N	UMBER	
			FEI	BRUAR	Y 24,	2000	
			DA	ГЕ			

09/486307 514 Rec'd PCT/PTO 2 4 FEB 2000

UNITED STATES PATENT AND TRADEMARK OFFICE

Examiner:

Group:

Attorney Docket #1041

Applicant(s):

Kreuzer, H.

Serial No.

Filed

Simultaneously

For

: ELECTRIC MACHINE, IN PARTICULAR A THREE-

PHASE GENERATOR

SIMULTANEOUS AMENDMENT

February 23, 2000

Honorable Commissioner of Patents and Trademarks Washington, D.C. 20231

SIRS:

Simultaneously with filing of the above identified application please amend the same as follows:

In the Claims:

Claim 3 line 1 and 2 delete "one of the preceding claims", substitute with "claim 1".

Claim 4 line 1 and 2 delete "one of the preceding claims", substitute with "claim 1".

Claim 5 line 1 and 2 delete "one of the preceding claims", substitute with "claim 1".

Claim 6 line 1 and 2 delete "one of the preceding claims", substitute with "claim 1".

REMARKS:

This Amendment is submitted simultaneously with filing of the above identified application.

With the present Amendment applicant has amended the claims so as to eliminate their multiple dependency.

Consideration and allowance of the present application is most respectfully requested.

Respectfully submitted,

Michael J. Striker

Attorney for Applicant(s) Reg. No. 27233

09/486307 514 Rec'd PCT/PTO 2 4 FEB 2000

VERIFICATION OF TRANSLATION

DAVID CLAYBERG

of 948 15th St., Ste. 4 Santa Monica, CA 90403-3134

declare that I am a certified translator well acquainted with both the German and English languages, and that the attached is an accurate translation, to the best of my knowledge and ability, of the German Patent Application PCT/DE 98/01914.

Signature

DAVID CLAYBERG

Date 23 FEB 2000

4/PRTS 1

09/486307 514 Rec'd PCT/PTO 24 FEB 2000

Electric Machine, in Particular a Three-Phase Generator

The invention relates to an electric machine, in particular a three-phase generator, with the characterizing features mentioned in the preamble to claim 1.

Prior Art

Electric machines that are embodied as three-phase generators are known. These are used, for example, for supplying power to the electrical system in motor vehicles. In this connection, an excitation winding disposed on a rotor is excited with a direct current. This produces a magnetic field, which is conducted to alternatingly disposed claw poles of a claw-pole rotor. Through the alternating disposition of the claw poles, the north and south poles of the magnetic field alternate with one another. The claw-pole rotor is encompassed by a stator which has a winding packet. In a three-phase generator, this winding packet is comprised of windings that are connected together in three-phase fashion, which are penetrated by the magnetic field in accordance with the rotation of the claw-pole rotor. This induces a voltage in the winding packet, which is tapped as the generator voltage in the windings that are respectively connected together into one phase. A three-phase generator that is constructed in this manner is described, for example, in DE 34 08 394 A1.

German Patent 254 680 has disclosed forming the windings of a winding packet from winding wires that are connected to one another in parallel.

Advantages of the Invention

The electric machine according to the invention, with the features mentioned in claim 1, offers the advantage that depending on the wiring of the winding packet, different levels of generator voltage can be tapped. By virtue of the fact that at least two of the at least three parallel wound winding wires of a phase are respectively connected to separate phase terminals, at each of which a respective partial generator voltage can be tapped, a partial generator voltage can be supplied as needed at the phase terminals associated with each phase. In a preferable embodiment of the invention, the provision is made that in order to tap a total generator voltage that is made up of the partial generator voltages, the phase terminals of a phase can be connected in series. By means of this, it is easily possible for the parallel wound windings to be connected in series by way of a switching means in order to thus produce a higher generator voltage when needed.

By and large, it is possible through simple means, which can be realized without intervention into the structural embodiment of the electric machine, to use an electric machine to supply different levels of generator voltage.

Other advantageous embodiments of the invention ensue from the remaining features that are mentioned in the dependent claims.

Drawings

The invention will be explained in detail below in exemplary embodiments in conjunction with the accompanying drawings.

- Fig. 1 is a schematic, partial view of a three-phase generator;
- Fig. 3 is an enlarged detail from the partial view, and
- Figs. 2, and 4 to 6 show wiring variations of the three-phase generator.

Description of the Exemplary Embodiments

Fig. 1 shows a schematic detail of a section through a three-phase generator 10. The three-phase generator 10 has clawpole rotor 14 disposed on a drive shaft 12 so that it is fixed against relative rotation. The claw-pole rotor 14 has claw poles 20 and 22 that alternatingly extend from pole disks 16 and 18 coaxial to the drive shaft 12. By means of an excitation winding not shown in Fig. 1 - disposed on the drive shaft 12, which winding is powered with direct current, the claw poles are magnetized so that magnetic north poles N and magnetic south poles S are disposed alternatingly over the circumference of the claw-pole rotor 12.

The claw-pole rotor 14 is encompassed by a stator 24, which supports a winding packet 26. The winding packet 26 is composed of a number of windings 28 which are disposed in grooves 30 of a stator lamination bundle 32.

According to other exemplary embodiments, not shown, the disposition of the winding packet 26 can deviate from the one depicted. It is crucial that the windings 28 are penetrated by the magnetic field emanating from the claw-pole rotor 14.

The windings 28 are comprised of winding wires 33 and 42, which are connected in a manner that will be explained below.

According to the number of claw poles 20 and 22 a corresponding number of windings 28 are provided, which in a three-phase generator, are connected together into three phases U, V, and W. The basic wiring diagram is shown in Fig. 2. According to this depiction, the windings 28 are connected in a star shape in three strands 28', 28", and 28"' so that the phase voltages u, v, and w can be respectively tapped at phase terminals 34, 36, and 38. It is clear that the winding strands 28', 28", and 28"' shown in Fig. 2 are constituted by a corresponding number of series connected windings 28 of the winding packet 26. As a result, partial generator voltages u', v', w' can be tapped between the series connected windings. Furthermore, other connections, for example a triangular connection, are also possible.

In an enlarged schematic depiction, Fig. 3 clearly shows that the windings 28 are constituted by the winding wires 33. A number of winding wires 33 are respectively combined into a conductor bundle 40, which is wound into the grooves 30 in a number of windings. This means that the winding wires 33 of the conductor bundles of the individual phases U, V, and W are respectively disposed in parallel and are connected together in the phase terminals 34, 36, and 38, respectively. In this connection, however, not all winding wires 33 are connected to

the phase terminals 34, 36, and 38, but at least one winding wire 42', 42", or 42"' of each phase U, V, W is connected to a separate phase terminal 34', 36', or 38'. Consequently, a load-independent phase voltage u', v', or w' can be tapped at the phase terminals 34', 36', and 38', respectively.

According to different exemplary embodiments, the number of the winding wires 33, which are connected together to the phases U, V, and W, or the number of winding wires 42, which are connected together to the phases U', V', and W', can vary. At least one out of all of the winding wires (winding wires 42) of the conductor bundle 40 is connected to the phases U', V', and W'. The winding wires 33 thus constitute a main winding 28 while the winding wires 42 constitute an auxiliary winding 44.

Fig. 4 depicts the circuit arrangement produced by the division into the main winding and auxiliary winding. The winding wires 42 are combined into windings 44 that produce the auxiliary winding.

According to the circuit arrangement shown in Fig. 4, either the generator (phase) voltages u, v, w present at the phases U, V, W or the generator (phase) voltages u', v', w' present at the phases U', V', W' can now be tapped as needed by way of external switching means that are not shown.

According to the circuit arrangement shown in Fig. 5, it is likewise possible to connect the windings 28 or 44 in series by way of switching means that are not shown so that the phase U'' is present at the phase terminal 34', the phase V'' is present at the phase terminal 36', and the phase W'' is present at the phase terminal 38'. Consequently, a generator voltage u'', v'', and w''

can be tapped, wherein the voltage u'' is made up of the sum of the voltages u and u', the voltage v'' is made up of the sum of the voltages v and v', and the voltage v'' is made up of the sum of the voltages v and v'.

Through simple means, it is possible to tap a total of three different generator voltages from the three-phase generator 10. Since the windings 28 and 44 are constituted by individual, i.e. at least one, parallel connected winding wires 33 and 42, the winding technique that is suited for a series production can also be used to manufacture the winding packet 26 without requiring changes in the winding technique or structural changes in the three-phase generator. Only the phase terminals 34', 36', and 38', which are also routed to the outside, and the switching means, which are necessary for the switching between the phase terminals 34, 36, 38 or 34', 36', and 38, must be additionally provided. Depending on the desired generator voltage, a simple switching can thus be used to change between a low voltage, a higher voltage, and a voltage made up of the sum of the two voltages. All of the winding wires 33 and 42 preferably have the same size cross section for the sake of better processing.

The production of the conductor bundle 40 from a large number of relatively thin winding wires 33 and 42, furthermore permits the grooves 36 to be filled to a greater degree so that by and large, it is possible to improve the efficiency of the three-phase generator 10.

In the exemplary embodiment according to Fig. 6, the windings of the phases R, S, T of a three-phase generator are respectively wound from one conductor bundle 40 into the grooves

of its stator winding packet, wherein each conductor bundle is comprised of three parallel connected winding wires 33 and a winding conductor 42 connected in series with it. In this embodiment, the consumers of the generator, in particular a rectifier circuit for supplying power to a d.c. battery in the vehicle, are connected to the main windings with the terminals U, V, and W, and a phase voltage that is twice as high is supplied at the terminals U', V', and W' of the auxiliary winding for control purposes and in order to supply power to the excitation winding of the generator. Since the winding beginnings and the winding ends are disposed at one and the same end face of the stator winding packet, it is easily possible to achieve the connection according to Fig. 6 there or in a connecting piece disposed there.

Claims

- 1. An electric machine, in particular a three-phase generator, with a winding packet that can be penetrated by a rotating magnetic field, wherein a number of windings of the winding packet are respectively connected together into at least one phase at which a generator voltage can be tapped, and the windings are comprised of a number of parallel wound winding wires, characterized in that out of the at least three parallel wound winding wires (33, 42) of a phase (U, V, W, U', V', W'), at least two are connected to separate phase terminals (34, 36, 38, 34', 36', 38') at each of which a partial generator voltage (u, v, w, u', v', w') can be tapped.
- 2. The electric machine according to claim 1, characterized in that the windings (28', 28", 28"'; 44', 44", 44"') of a phase (U, U'; V, V'; W, W') can be connected in series in order to tap a total generator voltage (u", v", w") that is made up of the partial generator voltages (u, u'; v, v'; w, w').
- 3. The electric machine according to one of the preceding claims, characterized in that the windings (28, 44) are constituted by a common conductor bundle (40).
- 4. The electric machine according to one of the preceding claims, characterized in that the windings (28) constitute a main winding and the windings (44) constitute an auxiliary winding.
- 5. The electric machine according to one of the preceding claims, characterized in that the main windings (28) have at least two parallel connected winding wires (33).


6. The electric machine according to one of the preceding claims, characterized in that the auxiliary windings (44) have at least one winding wire (42).

Abstract

The invention relates to an electric machine, in particular a three-phase generator, with a winding packet that can be penetrated by a rotating magnetic field, wherein a number of windings of the winding packet are respectively connected together into at least one phase at which a generator voltage can be tapped, and the windings are comprised of at least three parallel wound winding wires.

The provision is made that the parallel connected winding wires (33, 42) of a phase (U, V, W, U', V', W') are divided and connected to at least two separate phase terminals (34, 36, 38, 34', 36', 38') at each of which a partial generator voltage (u, v, w, u', v', w') can be tapped.

(Fig. 1)






Fig. 4

36¹




Fig. 5

4/4




Fig. 6

DECLARATION AND POWER OF ATTORNEY FOR NATIONAL STAGE OF PCT PATENT APPLICATION

As a below-named inventor, I hereby declare that: I

Helmut KREUZER

My residence, post office address and citizenship are as stated below next to my name.

I hereby state that I believe the named inventor or inventors in this Declaration to be the original and first inventor or inventors of the subject matter which is claimed and for which a patent is sought.

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose all information which is material to the patentability of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56.

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed.

Prior foreign application(s):

Priority claimed:

197 37 681,9	GERMANY	AUGUST 29, 1997	X	
(Number)	(Country)	(Date filed)	Yes	No
(Number)	(Country)	(Date filed)	Yes	No

As a named inventor, I hereby appoint the following attorney to prosecute this application and to transact all business in the Patent and Trademark Office connected therewith:

Michael J. Striker, Reg. No. 27233 Ilya Zborovsky, Reg. No. 28563 William G. Valance, Reg. No. 28275.

Direct all telephone calls to Striker, Striker & Stenby at telephone no.: (631) 549 4700 and address and all correspondence to:

STRIKER, STRIKER & STENBY 103 East Neck Road Huntington, New York 11743 U.S.A.

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that wilful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such wilful false statement may jeopardize the validity of the application or any patent issued thereon.

· · · · · · · · · · · · · · · · · · ·		,	
Signature: Hammet Kreuw	Date:	Residence and Full Postal Address: Hermann-Essig-Strasse 94	
Full Name of First or Sole Inventor: Helmut KREUZER	Citizenship: GERMAN	71701 Schwieberdingen DEX	
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Second Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Third Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Fourth Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Fifth Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Sixth Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Seventh Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Eighth Inventor:	Citizenship:		
Signature:	Date:	Residence and Full Postal Address:	
Full Name of Ninth Inventor:	Citizenship:		